




Alfa AC-250I

Receipt Printer



Multiple interface choice



1. Power
2. Serial port
3. USB
4. Ethernet
5. Cash drawer

Support paper near end and black mark detection;
Connect and printer faster, stop Receipt misprinting;
Mechanism and cutter integrated, more durable
Virtual serial port mode, USB port support OPOS application;
250 mm/sec ultra high print speed;
Built in Web page to set up printer directly;
Printer status monitoring
High speed driver printing mode, 66% improvement in print;
Windows X86 / X64 / Linux / OPOS driver;
Support up 68 international languages and GB1830;
Serial + USB, Ethernet

SPECIFICATIONS AT A GLANCE

Print method

Direct thermal line

Print width

64/76mm

Dot density

512/576dot/line

Print speed

250mm/s

Interface

Serial + USB + Ethernet (Standard)

Paper diameter

80mm

Line space

3.75mm(can be adjustable)

Character Size

ANK Font Font A: 12×24dots Font B: 9×17dots

Code page

Simplified/Traditional Chinese Character: 24×24dots

PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/

Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/

PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/

1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/

(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)

Barcode mode

UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/

CODABAR/CODE93/CODE128

Fonts

GB18030

Data

128K bytes

NV Flash

256K bytes

Cashdrawer out

DC 24V/1A

Power supply

AC 110V/220V, 50 ,60Hz , DC 24V/2.5A

Dimension

195×160×145mm

Work environment

Temperature:0 ~ 45°C , Humidity:10 ~ 80%

Storage environment

Temperature:-10 ~ 60°C , Humidity:10 ~ 90%

Auto Cutter

1 MILLION

Print head life

150KM



www.alfa-egy.com

