



## ALFA POS 2100



- High-end touch screen technology, surface main display 15 inches 1027\*768, 10-point touch;
- Capacitance 10-point touch screen, clear picture, solid screen surface;
- Support Windows, Linux operating system;
- The power on button is handy, the interface is easy to plug and unplug without affecting the appearance;
- Flexible configuration, rich interface, strong expansibility;
- Elegant and fashionable appearance, optimized design, ergonomic;
- Compact size, compact structure, saving space;





## Specification

|               |                   |                                                            |
|---------------|-------------------|------------------------------------------------------------|
| Model         |                   | POS 2100                                                   |
| Key Component | CPU               | 5 Generación CPU, I3-5010U/5005U                           |
|               | POS graphics      | Integrated Intel® HD5500 graphics controller               |
|               | Memory            | 4GB,MAX 8GB                                                |
|               | SSD               | 128GB SSD                                                  |
|               | Main screen       | 15" 1024*768                                               |
|               | touch screen      | Multipoint capacitive touch                                |
|               | Second display    | 15" 1024*768                                               |
|               | Operation         | Support Windows、Linux                                      |
| Port          | USB interface     | 2个USB3.0,2个USB2.0,extend 2个USB2.0                          |
|               | Com interface     | 2*COM (extend)                                             |
|               | Audio interface   | External audio, microphone interface                       |
|               | Display interface | 1* HDMI、1*VGA                                              |
|               | network interface | 10M/100M/1000M LAN Port                                    |
|               | DC IN             | 1*DC12V 5A                                                 |
|               | Other ( option )  | Support WiFi/Bluetooth/3G/4G                               |
| Others        | bottom case       | ABS                                                        |
|               | Front panel       | ABS                                                        |
|               | foundation        | ABS+Metal plate                                            |
|               | Work environment  | Work temperature: -20℃~60℃;<br>operating humidity : 5%~95% |

